

**DELHI POLLUTION CONTROL COMMITTEE**  
**DEPARTMENT OF ENVIRONMENT: GOVT. OF NCT OF DELHI**  
**5<sup>TH</sup> FLOOR: ISBT BUILDING: KASHMERE GATE: DELHI-6**

F.No.DPCC/5(9)(2)/CT-06/384

Dated: 11-02-2009

To

**Sub.: Renovation of toilet in the office of DPCC**

This office is in the process of renovation of the toilet attached with the Room no. 574 at 5<sup>th</sup> floor, ISBT Bldg. If you are interested you may send the quotation in a sealed cover super scribing "rates for renovation of toilets" latest by 3.00 p.m. on 24-02-09. Rate should be as per DSR. No quotation will be entertained other than DSR. Specification of the material of renovation work are as under:-

| S.No | Description of Items                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Qty.        |
|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|
| 1.   | Dismantling stone slab flooring laid in cement mortar including stacking of serviceable material and disposal of unserviceable material within 50 meters lead.                                                                                                                                                                                                                                                                                                       | 25.00 SQm.  |
| 2.   | Concealed pipe including painting with anti corrosive bit mastic paint, cutting chases and making good the wall"<br>a) 25 to 40 mm nominal bore                                                                                                                                                                                                                                                                                                                      | 10.00 Mtrs. |
| 3.   | Making connection of G.I. distribution branch with G.I. main of following sizes by providing and fixing tee, including cutting and threading the pipe etc. complete<br>a) 15 mm nominal bore                                                                                                                                                                                                                                                                         | 1 No.       |
| 4.   | Providing and fixing brass stop cock of approved quality.                                                                                                                                                                                                                                                                                                                                                                                                            | 2 Nos       |
| 5.   | Providing and fixing trap of self cleansing design with screwed down or hinged grating with or without vent arm complete, including cost of cutting and making good the walls and floor. A) 100 mm inlet and 100 mm outlet Sand cast iron S&S as per IS: 3989                                                                                                                                                                                                        | 2 Nos       |
| 6.   | Providing and fixing soil, waste and vent pipes:<br>a) 100 x 100 x 100 mm Sand cast iron S & S as per IS-1729                                                                                                                                                                                                                                                                                                                                                        | 3.00 Mtrs   |
| 7.   | Providing and fixing single equal plain junction of required degree:<br>a) 100x100x100mm Sand cast iron S & S as per IS-1729                                                                                                                                                                                                                                                                                                                                         | 1 Nos       |
| 8.   | Providing and fixing white vitreous china pedestal type water closet (European type W.C. flushing cistern with manually controlled device (handle lever), conforming to IS: 7231, with all fittings, and fixtures complete including cutting and making good the walls and floors wherever required.<br><br>a) W.C. pan with ISI marked white solid plastic seat and lid.                                                                                            | 1 Nos       |
| 9.   | Providing and fixing white vitreous china flat back or wall corner type lipped front urinal basin of 430 x260x350mm and 340x410x265mm sizes respectively with automatic flushing cistern with standard flush pipe and C.P. brass spreaders with brass unions and G.I. clamps complete, including painting of fittings and brackets, cutting and making good the walls and floors wherever required.<br>a) One urinal basin with 5 litre white PVC automatic flushing | 1 Nos       |

|     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |              |
|-----|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
|     | cistern.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |              |
| 10. | Providing and fixing wash basin with CI/MS brackets, 15 mm CP brass pillar taps, Kingston/Gem/Techno/Parko, 32 mm CP brass waste of standard pattern, including painting of fittings and brackets, cutting and making good the walls wherever required:<br>a) White Vitreous China flat back wash basin size 550x400 mm with single 15 mm CP brass pillar tapes                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 1 No         |
| 11. | Extra for using colored pedestal type W.C. pan (European type) with low level cistern of same colour instead of white vitreous china W.C. pan and cistern.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 2 No         |
| 12. | Providing and fixing mirror thickness of required shape and size with plastic moulded frame of approved make and shade with 6 mm thick hard board backing<br>a) Oval shape 450 X350 mm (outer dimensions)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 1 Nos.       |
| 13. | Providing and fixing 1st quality ceramic glazed wall tiles conforming to IS: 15622 (thickness to be specified by the manufacture) of approved make in all colours, shades except burgundy, bottle green, black of any size as approved by Engineer-in-charge in skirting, risers of steps and dados over 12 mm thick bed of cement mortar 1: 3 (1 cement:3 coarse sand) and jointing with grey cement slurry @ 3.3. Kg per sqm including pointing in white cement mixed with pigment of matching shade complete.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 16.00<br>SqM |
| 14. | Providing & laying ceramic glazed floor tiles 300x300 mm (thickness to be specified by the manufacturer) of 1st quality confirming to IS : 15622 of approved make in colours such as White, Ivory, Grey, Fume Red Brown, laid on 20 mm thick cement mortar 1:4 (1 cement: 4 coarse sand including pointing the joints with white cement and matching pigments etc, complete.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               | 5.00<br>SqM  |
| 15. | Providing & fixing aluminum work for door, windows, ventilators and partitions with extruded built-up standard tubular sections/appropriate Z section and other sections of approved make conforming to IS 733 and IS: 1285 fixed with raw plugs and screws or with fixing clips, or with expansion hold fasters including necessary filling-up of gaps at junctions, at top, bottom and side with required PVC/neoprene flat etc. Aluminum section shall be smooth, rust free, straight mitred and jointed mechanically wherever required including cleat angle, aluminum snap beading for glazing/paneling, CP brass/stainless steel screws, all complete as per architectural drawing and the directions of Engineer-in-Charge (Glazing and paneling to be paid for separately)<br>b) For shutters of door, windows & ventilators including providing and fixing hinges/pivots and making provision for fixing of fittings wherever required including the cost of PVC/neoprene gasket required (Fittings shall be paid for separately) Anodized aluminum (anodized transparent or dyed to required shade according to IS: 1868, minimum anodic coating of grade AC 15) | 2.1<br>SqM   |
| 16. | Providing and fixing at all height false ceiling including providing and fixing of frame work made of special sections power pressed from MS sheet and galvanized in accordance with zinc coating of grade 350 as per IS:277 and consisting of angle cleats of size 25 mm wide X 1.6 mm thick with flanges of 22 mm and 37 mm at 12.00 mm centre to centre one flange fixed to the ceiling with dash                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | 3.50<br>SqM  |

|     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |              |
|-----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
|     | <p>fastner 12.5 mm dia X40 mm long with 6 mm centre to centre one flange fixed to the ceiling with dash fastner 12.5 mm dia X40 mm long with 6 mm dia bolts to the angle hangers of 25x25x0.55 mm of required length, and other end of angle hanger being fixed with nut &amp; bolts to GI channels 45 X15X0.0 mm running at the rate of 1200 mm centre to centre to which the ceiling section 0.5 mm thick bottom wedge of 80 mm with tapered flanges of 26mm each having clips of 10.5 mm at 450 mm centre to centre shall be fixed in a direction perpendicular to GI channel with connecting clips made out of 2.64 mm dia X 230 mm long GI wire at every junction including fixing the gypsum board with ceiling section and perimeter channels 0.5 mm thick 27 mm high having flanges of 20 mm and 30 mm long, the perimeter of ceiling fixed to wall/partition with the help of raw plugs at 350 mm centre to centre with 25 mm long drive-all screws @ 230 mm interval including jointing and fixing to a flush finish of tapered and square edges of the board with recommended filler, jointing tapes, finisher and two coats of primer suitable for board as per manufactures specification and also including the cost of making openings for light fittings, grills, diffusers, cutouts made with frame of perimeter channels suitable fixed all complete as per drawing and specification and direction of the Engineer-in Charge but excluding the cost of painting.</p> <p>With 12.5 mm thick tapered edge gypsum board conforming to IS: 2095-Part-I</p> |              |
| 17. | <p>Painting with synthetic enamel paint of approved brand and manufacture of required colour to give an even shade.</p> <p>a) Two or more coats on new work over and under coat of suitable shade with ordinary paint of approved brand and manufacture.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 10.00<br>SqM |

Member Secretary, DPCC has reserve all right to accept or reject any or all quotations. Site may be inspected in any working day between 11.00 A.M. to 05.00 P.M. before submission of quotation.

**(H.P. MEENA)**  
**Admn. Officer**